





Medallion Fence

10651 KEELE STREET
 MAPLE, ONTARIO L6A 3Y9
 (T) 905-832-2922 | 1-800-794-1564 | (F) 905-832-1564
 info@medallionfence.com | www.medallionfence.com

Medallion Fence

Style:
 CAVALIER-DR-SF

Series:
 PRESTON™



SPECIFICATIONS

TUBE COMPOSITION - POSTS, RAILS & PICKETS

- Coated Cold Formed ERW Tubing
- With a coating designation being a minimum protective coating weight of 275gm/m² both interior and exterior
 - Top coat consisting of a chromium-free phosphate conversion coating
 - Coating conforming to ASTM A1046 for hot dip coatings comprising of Zinc, Aluminum and Magnesium
 - ERW tube conforming to ASTM A787 Type 6
 - Minimum Yield Strength 207 MPa and Minimum Tensile Strength 290 MPa
- Weld seams mill re-metalized

MATERIAL DIMENSIONS

PICKET	1" x 1" (25mm x 25mm) 16GA
RAILS	2-1/2" x 1-1/2" (64mm x 38mm) 16 GA
POSTS BASE-PLATED	3" x 3" (76mm x 76mm) 11 GA or 14 GA
OPTIONAL POST(1) REGULAR or BASE-PLATED	4" x 4" (102mmx102mm) 11 GA

WELDS	Stainless Steel Mig Weld
FITTINGS	12 Gauge Stamp Forged Finish as below
FITTING FASTENERS	JS1000 Plated Finish as below
OPTIONAL FASTENER	Tamper Proof Nuts

FINISH

GRADE	Super Durable Polyester Powder Coat
OPTIONAL PRIMER	Zinc Rich Epoxy Powder Coat
STANDARD COLOUR	SEMI-GLOSS - BLACK
OTHER COLOURS	Green, Brown, White, Antique Silver
CUSTOM COLOURS	Per Specifications

STANDARD HEIGHTS	4'-3" 1295mm	5'-3" 1600mm	6'-3" 1905mm	7'-3" 2210mm	8'-3" 2515mm	9'-3" 2819mm	10'-3" 3124mm
	Custom heights are available (upon request)						

STANDARD GATES	Passage, Double Entry, Cantilever
----------------	-----------------------------------

MATERIAL SPECIFICATIONS:
 ARMOUR-SHIELD™
 BY MEDALLION FENCE

PROTECTED BY



OPTIONAL CAST FINIAL



Fleur Des Lis (FF)

OPTIONAL POST CAPS



PYRAMID



BALL



SPIRAL