




Medallion Fence

10651 KEELE STREET
MAPLE, ONTARIO L6A 3Y9
(T) 905-832-2922 || 1-800-794-1564 || (F) 905-832-1564
info@medallionfence.com || www.medallionfence.com


Medallion Fence

STYLE:
CAVALIER-DR-SF-SDEO

SERIES:
WELLINGTON™



SINGLE-GATES OPENINGS
AS REQUIRED 36", 48"
OR 60" STANDARD




STANDARD POST SETTING - 96 1/2" [2452MM]
STANDARD PANEL WIDTH - 94 1/2" [2400MM]

3 1/2" [89MM][BETWEEN PICKETS]


7 1/2" [190MM]
3 1/2" [89MM]

56-1/4" [1429mm] for 75" H
44-1/4" [1124mm] for 63" H
32 1/4" [819MM] FOR 51" H


4" [102MM]




2" SQ POST-COLLAR
C/W 1/2" DIA X 4"
HINGE BOLT




1-1/4"SQ
FRAME-COLLAR




1-1/4" SQ
FINGER-LATCH



2" SQ.
GRAVITY-CATCH
(LOCKABLE)



PRECISION PUNCHED FULL
TUBE FOR PICKET INSERTION




DOUBLE-GATES OPENINGS AS
REQUIRED 72", 96" OR 120"
STANDARD


7 1/2" [190MM]
3 1/2" [89MM]

56-1/4" [1429mm] for 75" H
44-1/4" [1124mm] for 63" H
32 1/4" [819MM] FOR 51" H


4" [102MM]




2" SQ POST-COLLAR
C/W 1/2" DIA X 4"
HINGE BOLT



1-1/4"SQ
FRAME-COLLAR



1-1/4" SQ
FINGER-LATCH



2" SQ.
GRAVITY-CATCH
(LOCKABLE)

OPTIONAL CAST FINIAL




SPIRAL FINIAL (SF)




FLEUR DES LIS (FF)

BRACKET



MULTI-FUNCTIONAL
BRACKET



WOOD/MASONRY BRACKET


OPTIONAL POST CAPS



PYRAMID




BALL




SPIRAL

SWIVEL BRACKET




SWIVEL BRACKET



WOOD/MASONRY SWIVEL
BRACKET

PROTECTED BY



ARMOUR-SHIELD™

MATERIAL SPECIFICATIONS:

ARMOUR-SHIELD™
BY MEDALLION FENCE

SPECIFICATIONS

TUBE COMPOSITION - POSTS , RAILS & PICKETS

- MINIMUM YIELD STRENGTH: 45 KSI (310 MPA)
- MINIMUM TENSILE STRENGTH: 55 KSI (380 MPA)
- ASTM A787 (TUBE)
- TUBE MANUFACTURED FROM PRE-COATED ALUMINUM-ZINC COATED STEEL WITH COATING DESIGNATION AZ50 CONFORMING TO ASTM A792/A792M

MATERIAL DIMENSIONS

PICKET	3/4" x 3/4" (19mm x 19mm) 18 GA
RAILS	1-1/4" x 1-1/4" (32mm x 32mm) 16 GA
POSTS REGULAR or BASE-PLATED	2" x 2" (51mm x 51mm) 16 GA or 14 GA
OPTIONAL POST REGULAR or BASE-PLATED	2-1/2" x 2-1/2" (64mmx64mm) 14 GA
UPRIGHTS	1-1/4" x 1-1/4" (32mm x 32mm) 16 GA or 14 GA

WELDS	Stainless Steel Mig Weld
FITTINGS	14 Gauge Stamp Forged Finish as below
FITTING FASTENERS	JS1000 Plated Finish as below
OPTIONAL FASTENER	Tamper Proof Nuts

FINISH

GRADE	Super Durable Polyester Powder Coat
OPTIONAL PRIMER	Zinc Rich Epoxy Powder Coat
OPTIONAL PRIMER (2)	E-Coat
STANDARD COLOUR	SEMI-GLOSS - BLACK
OTHER COLOURS	Green, Brown, White, Antique Silver
CUSTOM COLOURS	Per Specifications

STANDARD HEIGHTS	NA	NA	51" 1295mm	63" 1600mm	75" 1905mm
	Custom heights are available (upon request)				

STANDARD GATES	Passage, Double Entry, Cantilever
----------------	-----------------------------------

STANDARD POST SETTING & PANEL WIDTH

FOR FENCE HEIGHTS	PANEL WIDTH	POST SPACING [OPENING]
Up to 6' [1829mm]	94 1/2" [2400MM]	96 1/2" [2452 MM]
Over 6' [1829mm]	NA	